



Selectable Gallonage

Selectable Gallonage

The Thunderfog is available in two basic series: the 200 series, with a selectable flow range of 30-200 GPM, and the 250 series, with a selectable flow range of 95-250 GPM. The 200 series is an excellent choice for 1-1/2 or 1-3/4" hose lines, and for higher flows, the 250 series will work with 1-1/2" through 2-1/2" lines. All Thunderfogs are NFPA compliant, and are available in tip only configuration, or with stainless steel ball shutoff and optional colour-coded pistol grips. All Thunderfogs accept the FJ-MX-FT FOAMJET Multi expansion foam aspirating attachment, and come with your choice of fixed or stainless steel spinning fog teeth.

FTS250PS

Selectable gallonage nozzle with five flow settings of 95, 125, 150, 200, and 250 GPM @ 100 PSI. All lightweight materials, hardcoat anodised aluminium. Flush without shutting down. Quickchange rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. 1-1/2" NH full-time swivel is standard. Stainless steel spinning teeth.






Product Shot

Dual Gallonage

The 1" Twister is a selectable, dual gallonage combination nozzle, available in 3/4" or 1" threads, and designed for simplicity and durability. The rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, then high flow fog. The Twister, with its optional colour-coded pistol grip, is a rugged economical nozzle that will accept the FJ-MX-D FOAMJET Multiexpansion foam aspirating attachment.




DS1040P

Dual gallonage nozzle with two flow settings of 10 and 40 GPM @ 100 PSI. All lightweight materials, hard coat anodised aluminium. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve 1" NH swivel is standard.

Dual Gallonage

The 1 1/2" Twister is a selectable, dual gallonage combination nozzle available in 1 1/2" threads, and designed for simplicity and durability. The rubber bumper provides a positive grip and protects the fixed metal fog teeth. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, then high flow fog. The Twister, with its optional coloured-coded pistol grip, is a rugged, economical nozzle that will accept the FJ-MX-F FOAMJET multi-expansion foam aspiration attachment.



FS2095P

Dual gallonage nozzle with two flow settings of 20 and 95 GPM @ 100 PSI. All lightweight materials, hard coat anodised aluminium. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve. 1-1/2" NH swivel is standard.

Contact Us

Phone 03 9466 1244

Email gaam.au@tycoint.com

Website www.gaam.com.au

GAAM
Emergency Products