



Nozzles

WAMK-17 Polycarbonate Nozzle 38 mm (1 1/2") NPSH

This lightweight, corrosion resistant and durable 12,7 mm (1/2") nozzle comes with combination tips with 6 mm (1/4") and 10 mm (3/8") orifices. Nozzle is smooth bored for more effective and uniform water stream. Flame resistant and ribreinforced for strength and gripping. Bright yellow polycarbonate (plastic) Supplied with two 12,7 mm (1/2") and one 38 mm (1 1/2") rubber gaskets. 38 mm (1 1/2") female NPSH inlet and 12,7 mm (1/2") orifice male NPSH outlet. 23 cm (9") long. 142 g (5 oz).

Options :

- > B-4254-M Nozzle only
- > B-4315 Tip set only
- > Also shown : MK-175-MI with FA-3 38 mm (1 1/2") 1/4 -turn quick connection



WAMK-177 - Aluminium Nozzle 38 mm (1 1/2") NPSH

This lightweight, corrosion resistant and durable 12,7 mm (1/2") nozzle comes with combination tips with 6 mm (1/4") and 10 mm (3/8") orifices. Flame resistant, it is designed to withstand 4 136 kPa (600 psi) test pressure. Anodized aluminium alloy (to minimize thread seizures). Supplied with two 12,7 mm (1/2") and one 38 mm (1 1/2") rubber gaskets. 38 mm (1 1/2") female NPSH inlet and 12,7 mm (1/2") male NPSH outlet. 23 cm (9") long. 283 g (10 oz).

Options :

- > C-1933 Nozzle only
- > A-5911 Tip set only
- > Also available : MK-177-MI with FA-3 38 mm (1 1/2") 1/4 -turn quick connection.





WAW-225B - Nozzle Combination Spray/Straight Stream

Lightweight, corrosion resistant and durable nozzle. Flame resistant and ribreinforced for strength and gripping. Bright yellow polycarbonate (plastic). Supplied with 38 mm (1 1/2") rubber gasket (12-43). 38 mm (1 1/2") female NPSH inlet and 11 mm (7/16") maximum orifice straight stream, adjustable spray outlet. 14 cm (5 1/2") long. 226 g (8 oz). Also shown : W-225B-MI with FA-3 38 mm (1 1/2") 1/4 - turn quick connection, 340 g (12 oz).



WAF-407 - Variable Flow Nozzle

Light, compact, corrosion resistant solid brass with stainless steel construction. Eliminates changing nozzle tips. Designed for 19 mm (3/4") garden hose thread GHT coupling, it can produce solid stream, spray, mist or shut-off by simply turning the nozzle's tips. Built-in nozzle gasket for trouble-free use. 80 g (3 oz).



WAA-6877 - Nozzle Multi-Aperture

This lightweight corrosion resistant and durable nozzle is designed to withstand the high pressure requested by forestry applications. The multi-aperture eliminates changing nozzle tips. Anodized aluminium alloy. Nozzle bore sizes of 3, 5, 6, 8 mm (1/8", 3/16", 1/4", 5/16") and shut-off. 53 mm (2.10") barrel diameter. 127 mm (5") long. 350 g (12.3 oz).



WAB-2066 - Universal Hose Wrench

For use in coupling and uncoupling 25 mm (1"), 38 mm (1 1/2"), 51 mm (2") hose line couplings, swivel hose fittings, pin or rocker lug couplings. Light, corrosion resistant anodized alloy 180 mm (7"). 128 g (4 1/2 oz).



WAB-7380 - Universal Hose Wrench - Double Ended

Offers the universal hose wrench B-2066 characteristics with the added features required for 1/4-turn short lugs. Specially designed to couple and uncouple 1/4-turn short lugs in a quick, easy and safe manner. Also, it can be used to couple and uncouple 25 mm (1"); 38 mm (1 1/2"); 51 mm (2") hose line couplings, swivel hose fittings and rocker lug couplings. Light, corrosion resistant anodized alloy. 158 mm (6 1/4") 145 g (5 oz).

Contact Us

Phone 03 9466 1244

Email gaam.au@tycoint.com

Website www.gaam.com.au

GAAM
Emergency Products