



## Accessories

### WAHT1250

**Hose Tester** The smallest hose tester. It fills hose from a 38 mm (1/2") NST supply line then pressurizes through a 6,4 mm (1/4") opening in compliance with NFPA # 1962. Equipped with 38 mm (1 1/2") NST adaptors, the hose tester will arrive ready to test hose of any size. Includes;

- > Powerful 1 HP wet environment motor
- > 8,3 L/min (1.8 IMP gals, 2.2 US gals) oil bath pump
- > Delivers up to 5600 kPa (800 psi) pressure
- > Fully automatic check valve system (reduces labour and increases safety)
- > 38 mm (1 1/2") swivel inlet connector
- > Free 38 mm (1 1/2") NST adaptors on all four outlets
- > All stainless 25 mm (1") 17 237 kPa (2500 psi) manifold
- > Complies with NFPA standard

### WAA5825

**Fire Hose Washer** Remarkably effective in cleaning all types of dirty caked-up fire hose. No adjustments of flow or pressure required. Once in operation the washer works automatically at full efficiency. There is no contact between hose and washer since hose is supported by powerful water jets providing pressure is 420 kPa (60 psi) or more. The hose is passed through body against water stream so that dislodged dirt particles are carried away from clean hose. Supplied with 38 mm (1 1/2") female swivel NPSH. Capable of washing hose up to 76 mm (3").



### Expansion Rings and Rubber Gaskets

**Hose Thread Gaskets** Gaskets are square edge, lathe cut 60-65 Durometer neoprene for resilient long life. Standard sizes are given but special sizes are available.

Cat. No.	Thread Size	I.D.	O.D.	Thickness
WAMK197	19 mm (3/4") GHT	20 mm	27 mm	3 mm
WAMK176	25 mm (1") BSP	26 mm	35 mm	3 mm
WAMK176A	25 mm (1") NH	26 mm	37 mm	3 mm
WA1243	38 mm (1 1/2") BSP	38 mm	51 mm	3 mm
WAMK138	51 mm (2") NH	52 mm	64 mm	3 mm

### Hose Bowl Gaskets

Used inside the coupling bowl to prevent leakage between the hose jacket and expansion ring. Due to the number of coupling manufacturers there are too many sizes available to list separately, we only list coupling type ; your size would fall into one of these categories.

Rubber Lined Cat. No.	Thread Size
WAMK139	25 mm (1") - Single jacket
WAMK133	38 mm (1 1/2") - Single jacket or double jacket

### Brass Expansion Rings

Made from a special tempered seamless brass tubing with smooth chamfered edges to give trouble free coupling.

No.	Size O.D	Length	Thickness
WAJM117	25 mm	22 mm	1,1 mm
WAAG306	25 mm	32 mm	1,1 mm
GA9218B	38 mm	22 mm	1,3 mm
WAMK135	38 mm	27 mm	1,3 mm
WAMK125YB	38 mm	22 mm	1,3 mm
WAER175x125	44 mm	22 mm	1,3 mm
WAMK137	51 mm	35 mm	1,6 mm
WAMK250	64 mm	38 mm	1,6 mm

Phone 03 9466 1244 | Email [gaam.au@tycoint.com](mailto:gaam.au@tycoint.com) | Website [www.gaam.com.au](http://www.gaam.com.au)