



## CROSSFIRE MONITOR

Crossfire Monitor

The Crossfire monitor is the most versatile and innovative master stream appliance ever offered to the fire service. Its lightweight, compact design and unique quick-release swivel joint allow for a faster and safer stream deployment in the portable attack mode. The Safe-Tak 1250 utilizes the revolutionary, patent pending Safe-Tak "flow safety valve". Should the monitor lose contact with the ground surface, the Safe-Tak will automatically reduce flow to the monitor. This safety feature reduces the risk of injury from an out-of-control appliance. Monitor top and base are hardcoat anodised aluminium with TF powder coat finish inside and out.



### XFT-NJ

CROSSFIRE MONITOR TOP can be connected to either a portable base or a truck with adapters. The connection is easy, positive, and visually verified. When in use, the release is "locked out" by water pressure. The waterway is a large 3.25" which lets the Crossfire deliver up to 1250 GPM with low friction loss.

Horizontal rotation is securely locked with a simple lever, and position can be visually confirmed. Only seven (7) turns of the handwheel change the discharge elbow from vertical to the stop elevation. Includes highly visible pressure gauge and built-in automatic drain valve. Standard outlet thread is male 2.5" NH.



### XFH-2NJ

The SAFE-TAK 1250 PORTABLE BASE is supplied with either two clappered swivel inlets or with a single full-time swivel inlet. The stainless steel, carbide-tipped base support legs can be folded to easily fit inside a small apparatus compartment, or for carrying preconnected to a hose line. Includes a safety tie down strap with attached storage cap.

**GAAM**   
Emergency Products