



## Fire Hose Connections

### WASA-45

Siamese (Dual), 38 mm (1 1/2") NPSH Swivel nuts rotate on ball bearings for ease of connection and to minimize cross threading. Unrestricted flow. The 38 mm (1 1/2") double male adaptor nipples attached with chains makes it possible to use as a wye (1 into 2) or as a wye (2 into 1). Designed to withstand 4 136 kPa (600 psi) test pressure. Light, corrosion resistant anodized alloy, painted bright red colour. Supplied with three 38 mm (1 1/2") rubber gaskets (12-43). Three hard anodized swivel nuts 38 mm (1 1/2") NPSH and two rocker lug swivel hose fittings 38 x 38 mm (1 1/2" x 1 1/2") male adaptor nipples NPSH A-2958. 908 g (2 lbs).



### WASA-50

Siamese, 38 mm (1 1/2") NPSH Forestry plain threaded siamese less valves, for 2 into 1 operation. Unrestricted flow. Swivel nuts rotate on ball bearings for ease of connection and to minimize cross threading. Designed to withstand 4 136 kPa (600 psi) test pressure. Light, corrosion resistant anodized alloy, painted bright red colour. Supplied with two 38 mm (1 1/2") rubber gaskets 12-43. Two hard anodized rocker lug swivel hose fittings 38 mm (1 1/2") female NPSH inlet and one 38 mm (1 1/2") male NPSH outlet. 680 g (1 1/2 lbs).



### WASA-25

Siamese Combination, 38 mm (1 1/2") Can be used for 1 into 2 or 2 into 1 operation. Unrestricted flow. Designed to withstand 4 136 kPa (600 psi) test pressure. Light, corrosion resistant anodized alloy, painted bright red colour. 38 mm (1 1/2") wye equipped with three 38 mm (1 1/2") 1/4 - turn quick connection FA-4 and sealing gaskets. 680 g (1 1/2 lbs).



### WASA-15

Wye, 38 mm (1 1/2") NPSH For 1 into 2 operation. Unrestricted flow. Swivel nut rotates on ball bearings for ease of connection and to minimize cross threading. Designed to withstand 4 136 kPa (600 psi) test pressure. Light, corrosion resistant anodized alloy, painted bright red colour. Supplied with 38 mm (1 1/2") rubber gasket 12-43. One hard anodized rocker lug swivel hose fitting 38 mm (1 1/2") female NPSH inlet and two 38 mm (1 1/2") male NPSH outlet. 0,45 kg (1lb).



### WASA-200

Wye Ball Valve, 38 mm (1 1/2") NPSH For 1 into 2 operation. Unrestricted flow. Swivel nut rotates on ball bearings for ease of connection and to minimize cross threading. Designed to withstand 4 136 kPa (600 psi) test pressure. Two ball valves enable independent line control. Balls adjust automatically to compensate for wear. Light, corrosion resistant anodized alloy, painted bright red colour. Supplied with 38 mm (1 1/2") rubber gasket 12-43. One hard anodized rocker lug swivel hose fitting 38 mm (1 1/2") female NPSH inlet and two 38 mm (1 1/2") male NPSH outlet. 1,6 kg (3 1/2 lbs).



### WASA-210

Siamese Ball Valve, 38 mm (1 1/2") 1/4-Turn For 1 into 2 or 2 into 1 operation. Unrestricted flow. Equip- ped with 1/4-turn quick connection and sealing gaskets. Designed to withstand 4 136 kPa (600 psi) test pressure. Two ball valves enable independent line control. Balls adjust automatically to compensate for wear. Light, corrosion resistant anodized alloy, painted bright red colour. Three 38 mm (1 1/2") NPSH openings with three 38 mm (1 1/2") instantaneous adaptors. 1,8 kg (4 lbs).



### WASA-250

Wye Ball Valve, 63 mm (2 1/2") NPSH Swivel nut 63 mm (2 1/2") rotates on ball bearings for ease of connection and to minimize cross threading. Unrestricted flow. Designed to withstand 4 136 kPa (600 psi) test pressure. Two ball valves enable independent line control. Balls adjust automatically to compensate for wear. Light, corrosion resistant anodized alloy, painted bright red colour. Supplied with 63 mm (2 1/2") gasket. One hard anodized rocker lug swivel hose fitting 63 mm (2 1/2") female inlet (thread to meet your requirement) and two 38 mm (1 1/2") male NPSH outlets. 1,8 kg (4 lbs).



### WASA-100

Wye Ball Valve, 25 mm (1") NPSH For 1 into 2 operation. Unrestricted flow. Designed to withstand 4 136 kPa (600 psi) test pressure. Two ball valves enable independent line control. Balls adjust automatically to compensate for wear. Light, corrosion resistant anodized alloy, painted bright red colour. Supplied with 25 mm (1") rubber gasket. One ball bearing rocker lug swivel hose fitting 25 mm (1") female NPSH inlet and two 25 mm (1") male NPSH outlet. 1,6 kg (3 1/2 lbs).



#### Contact Us

Phone 03 9466 1244

Email [gaam.au@tycoint.com](mailto:gaam.au@tycoint.com)

Website [www.gaam.com.au](http://www.gaam.com.au)

**GAAM**  
Emergency Products