



GAAM Godiva World Series Pump

Godiva World Series Pump

Vehicle Mounted Pumps

Designed by professionals for the most arduous of conditions, Godiva fire pumps have become the preferred choice for those seeking optimum design, build and efficiency levels. Now lighter and more powerful than ever, this comprehensive range of vehicle mounted pumps respond effectively to the challenges of an increasingly demanding environment, leading firefighting technology to new heights of excellence in both single and multipressure applications.

Key Features

- > Optimised efficiency levels.
- > Reduced size and weight.
- > Available in light alloy or gunmetal construction.
- > Close liaison with vehicle manufactures facilitates ease of installation.
- > Wide range of available specifications, from 1,6000 1/min to 10,000 1/min.
- > High durability of materials leading to longer life, with simple and rugged construction.
- > Wide range of options.
- > Low maintenance designs.
- > Full compliance with wide range of International Standards.






demonstration of product in use

| Performance Data | WT2010 | WT3010 | WT4010 |
|---|-------------------|-------------------|-------------------|
| Priming Performance Range | To 8m (26') | To 8m (26') | To 8m (26') |
| Priming Speed Range | 100 – 2700rpm | 100 – 2700rpm | 100 – 2700rpm |
| Maximum Suction Pressure | 12 bar | 12 bar | 12 bar |
| Maximum Recommended Speed | 3600 rpm | 3600 rpm | 3600 rpm |
| Maximum Outlet Pressure – Low Pressure | 16.5 bar | 16.5 bar | 16.5 bar |
| Maximum Outlet Pressure – High Pressure | 55 bar | 55 bar | 55 bar |
| Maximum Flow – Low Pressure | 3400 l/min | 4200 l/min | 6200 l/min |
| Maximum Flow – High Pressure | 750 l/min | 750 l/min | 750 l/min |
| Weight | 105 kg | 112.5 kg | 145.5 kg |
| Typical Dimensions (L x H x W) | 772 x 620 x 494mm | 790 x 620 x 720mm | 820 x 690 x 720mm |
| Priming Times to 7.5m | 22 sec | 32 sec | 32 sec |
| Thermal Relief Valve Activation | 48°C | 48°C | 48°C |
| Direction of Pump Rotation | To | Customer | Specification |

Basis of Data: 2010 with Piston Primer, 2 UK Valves, 4" suction. 3010/4010 with Piston Primer, 4 UK Valves, 5 1/2" Suction




Typical high-pressure performance of Godiva World Series multi-pressure vehicle mounted pump range at 3m lift.

Rated performance

| WT2010 | WT3010 | WT4010 |
|------------|------------|------------|
| 2000 L/min | 3000 L/min | 4000 L/min |
| At 10 bar | At 10 bar | At 10 bar |
| 3m lift | 3m lift | 3m lift |

Options

- Water Ring primer
- World Series Control Panel
- Reverse rotation
- Range of couplings and delivery valves
- Pneumatically activated crossover valve



Typical low-pressure performance of WT30/10 at 3m lift

GAAM Emergency Products policy is one of continuous improvement. We therefore reserve the right to amend specifications without notice or obligation.

Contact Us

Phone 03 9466 1244

Email gaam.au@tycoint.com

Website www.gaam.com.au

