



NUPLA POLES

Pike Poles

A traditional pike pole fitted to a NUPLAGLAS pole constructed of millions of fibreglass strands pultruded over a Honeycomb core provides the strength of our traditional featherlight pike poles.

Offers the strength, safety and durability benefits, yet is even more rigid to make it easier to manoeuvre.

Flame Resistance: NUPLAGLAS is flame resistant to 426°C, resists continuous heat to 121°C and improves in strength down to -15°C.

Strength: NUPLAGLAS HANDLES are stronger than wood handles

Safety:

- > Safe from electrical shock - NUPLAGLAS is an excellent dielectric material.
- > Smooth, resin rich surface protects user from splinters and resists UV deterioration.

Durability:

- > Does not absorb moisture, resists industrial chemicals, fire retardant
- > Easily cleaned of concrete, tar, etc.
- > Unaffected by sub zero temperatures.

Comfort:

- > Does not conduct heat / cold, easy to handle in extreme temperatures.
- > Ergonomically designed grips for comfort and stress reduction.
- > More rigid than wood and most other fibreglass handles, reducing wasted effort.

PART No. DESCRIPTION

PIKE POLES WITH BUTT GRIP END

NU36-203	914 mm long
NU36-204	1210 mm long
NU36-206	1820 mm long
NU36-208	2430 mm long
NU36-210	3040 mm long
NU36-212	3650 mm long
NU36-214	4260 mm long
NU36-216	4870 mm long

PIKE POLES WITH ALUMINIUM 'D' GRIP END

NU36-123	914 mm long
NU36-124	1210 mm long
NU36-126	1820 mm long
NU36-128	2430 mm long
NU36-130	3040 mm long
NU36-132	3650 mm long
NU36-134	4260 mm long
NU36-136	4870 mm long

CEILING/WALL POLES WITH BUTT GRIP END

NU35-470	1210 mm long
NU35-257	1820 mm long
NU35-574	2430 mm long
NU35-580	3040 mm long
NU35-586	3650 mm long
NU35-592	4260 mm long
NU35-598	4870 mm long

CEILING/WALL POLES WITH ALUMINIUM 'D' GRIP END

NU35-572	1210 mm long
NU35-573	1820 mm long
NU35-576	2430 mm long
NU35-582	3040 mm long
NU35-588	3650 mm long
NU35-594	4260 mm long
NU35-600	4870 mm long



Phone 03 9466 1244 | Email gaam.au@tycoint.com | Website www.gaam.com.au