



## Couplings

### WAA7113

Coupling - Adaptor, Female 38 mm (1 1/2") to 38 mm (1 1/2") Designed to withstand 4136 kPa (600 psi). It comes with a neoprene grooved gasket Wafa 12 and a rubber gasket WA1243. Light, corrosion resistant anodized aluminium alloy. 38 mm (1 1/2") female BSP to 38 mm (1 1/2") 1/4-turn quick-connect.

#### Options:

WAA7099 19 mm (3/4") female BSP to 38 mm (1 1/2") 1/4-turn quick-connect.  
Wafa4N Forged ULC approved 38 mm (1 1/2") female BSP to 38 mm (1 1/2") 1/4-turn quick-connect. Other sizes, combination and thread types available.



### WAA7019

Coupling - Adaptor, Female 25 mm (1") to 38 mm (1 1/2") Designed to withstand 4136 kPa (600 psi). It comes with a neoprene grooved gasket Wafa 12 and a rubber gasket WAMK 176. Light, corrosion resistant anodized aluminium alloy. 25 mm (1") female BSP to 38 mm (1 1/2") 1/4-turn quick-connect. Other sizes, combination and thread types available.



### WAA7114

Coupling - Adaptor, Male 38 mm (1 1/2") to 38 mm (1 1/2") Designed to withstand 4 136 kPa (600 psi). It comes with a neoprene grooved gasket WAF A12. Light, corrosion resistant anodized aluminium alloy. 38 mm (1 1/2") male BSP to 38mm (1 1/2") 1/4-turn quick -connect.

#### Options :

WAA7098 19 mm (3/4") male BSP to 38 mm (1 1/2") 1/4-turn quick -connect. WAF A3N Forged ULC approved 38 mm (1 1/2") male BSP to 38 mm (1 1/2") 1/4-turn quick -connect. Other sizes, combination and thread types available.



### WAA7018

Coupling - Adaptor, Male 25 mm (1") to 38 mm (1 1/2") Designed to withstand 4 136 kPa (600 psi). It comes with a neoprene grooved gasket (WAF A12). Light, corrosion resistant anodized aluminium alloy. 25 mm (1") male BSP to 38 mm (1 1/2") 1/4-turn quick -connect. Other sizes, combination and thread types available.



### WAF A13

Coupling - Blanking Plug To close 38 mm (1 1/2") 1/4 -turn quick -connect couplings, adaptors and fittings. Designed to withstand 4 136 kPa (600 psi). It comes with a neoprene grooved gasket FA-12. Light, corrosion resistant anodized aluminium alloy



### WAF A7

Coupling 1/4-Turn Quick-Connect Coupling for 38 mm (1 1/2") single jacket fire hoses. Supplied with neoprene grooved gasket WAF A12, hose bowl gasket WAMK133 and expansion ring WAMK135. Light corrosion resistant anodized aluminium alloy.

Option :

WAF A7N Forged ULC approved coupling set



#### Contact Us

Phone 03 9466 1244

Email [gaam.au@tycoint.com](mailto:gaam.au@tycoint.com)

Website [www.gaam.com.au](http://www.gaam.com.au)

**GAAM**   
Emergency Products



Product Shot



### WAFAB

Coupling 1/4-Turn Quick-Connect Coupling for 25 mm (1") single jacket fire hoses. Supplied with neoprene grooved gasket WAFAB12, hose bowl gasket WAMK139 and expansion ring WAJM117. Light, corrosion resistant anodized aluminium alloy.



### WAMK129

Coupling - Brass Rocker Lug 38 mm (1 1/2") Heavy-duty cast brass coupling for single jacket fire hoses. Supplied with expansion rings WAMK135, hose bowl gasket WAMK133 and rubber gasket WA1243. Male and female rocker lug, 38 mm (1 1/2") BSP.



### WAA6888B

Coupling - Adaptor, Female 51 mm (2") to 38 mm (1 1/2") Specially designed for tandem pumping, it can withstand 4136 kPa (600 psi). It comes with a rubber gasket MK-138 and neoprene grooved gasket FA-12. Light, corrosion resistant anodized aluminium alloy with hard anodized rocker lug, 51 mm (2") female BSP to 38 mm (1 1/2") 1/4-turn quick-connect. Other sizes, combination and thread types available.



### WAFAB12

Neoprene Grooved Gasket For 38 mm (1 1/2") 1/4-turn quick-connect couplings, adaptors and fittings.

#### Contact Us

Phone 1300 552 559

Email [gaam.au@tycoint.com](mailto:gaam.au@tycoint.com)

Website [www.gaam.com.au](http://www.gaam.com.au)

**GAAM**  
Emergency Products