Couplings

WAA7113

Coupling - Adaptor, Female 38 mm (1 1/2") to 38 mm (1 1/2") Designed to withstand 4136 kPa (600 psi). It comes with a neoprene grooved gasket WAFA12 and a rubber gasket WA1243. Light, corrosion resistant anodized aluminium alloy. 38 mm (1 1/2") female BSP to 38 mm (1 1/2") 1/4-turn quick -connect.

Options:
WAA7099 19 mm (3/4") female BSP to 38 mm (1 1/2") 1/4-turn quick - connect. WAFA4N Forged ULC approved 38 mm (1 1/2") female BSP to 38 mm (1 1/2") 1/4-turn quick-connect. Other sizes, combination and thread types available.

WAA7019

Coupling - Adaptor, Female 25 mm (1") to 38 mm (1 1/2") Designed to withstand 4136 kPa (600 psi). It comes with a neoprene grooved gasket WAFA12 and a rubber gasket WAMK176. Light, corrosion resistant anodized aluminium alloy. 25 mm (1") female BSP to 38 mm (1 1/2") 1/4-turn quick-connect. Other sizes, combination and thread types available.

WAA7114 KIT

Coupling - Adaptor, Male 38 mm (1 1/2") to 38 mm (1 1/2")Designed to withstand 4136 kPa (600 psi). It comes with a neoprene grooved gasket WAFA12. Light, corrosion resistant anodized aluminium alloy. 38 mm (1 1/2") male BSP to 38mm (1 1/2") 1/4-turn quick -connect.

Options :
WAA7098 19 mm (3/4") male BSP to 38 mm (11/2") 1/4-turn quick -connect. WAFA3N Forged ULC approved 38 mm (1 1/2") male BSP to 38 mm (11/2") 1/4-turn quick -connect. Other sizes, combination and thread types available.

GAAM Emergency Products

WAA7018

Coupling - Adaptor, Male 25 mm (1") to 38 mm (1 1/2") Designed to withstand 4136 kPa (600 psi). It comes with a neoprene grooved gasket (WAFA12). Light, corrosion resistant anodized aluminium alloy. 25 mm (1") male BSP to 38 mm (1 1/2") 1/4-turn quick - connect. Other sizes, combination and thread types available.

WAFA13

Coupling - Blanking Plug To close 38 mm (1 1/2") 1/4 -turn quick -connect couplings, adaptors and fittings. Designed to withstand 4136 kPa (600 psi). It comes with a neoprene grooved gasket FA-12. Light, corrosion resistant anodized aluminium alloy

WAFA7

Coupling 1/4-Turn Quick-Connect Coupling for 38 mm (1 1/2") single jacket fire hoses. Supplied with neoprene grooved gasket WAFA12, hose bowl gasket WAMK133 and expansion ring WAMK135. Light corrosion resistant anodized aluminium alloy.
Option : WAFA7N Forged ULC approved coupling set

WAFA8

Coupling 1/4 -Turn Quick-Connect Coupling for 25 mm (1") single jacket fire hoses. Supplied with neoprene grooved gasket WAFA12, hose bowl gasket WAMK139 and expansion ring WAJM117. Light, corrosion resistant anodized aluminium alloy.

WAFA12

Neoprene Grooved Gasket For 38 mm (1 1/2") 1/4-turn quick - connect couplings, adaptors and fittings.

Contact Us
Phone 03 9464 8400
Email gaam.au@tycoint.com
Website www.gaam.com.au

GAAM Emergency Products