



## Fire Hose Connections- Wyes & Siamese

### 65mm-2 1/2" GATED SIAMESE

The Jumbo Wye and Siamese incorporates TFT's unique aluminum half-ball design providing up to 500gpm efficiently through its dual valved 2 1/2" discharges. Color coded super tough nylon folding handles are standard and these lightweight hard anodized and powder coated appliances can be ordered with your choice of inlet and outlet couplings.

Also available in 100mm (4') 125mm (5') 150mm (6') Storz



### GATED WYE 2.5" x 1.5" (65mm x 38mm) OUTLETS

2.5" (65mm) female swivel inlet x two 1.5" (38mm) male outlets. Quarter-turn aluminum ball valves provide a positive shutoff. Full flow 1.5" (38mm) ball waterway. Rugged lightweight aluminum alloy casting with durable powder coat finish inside and out, anodized couplings, and super tough nylon folding handles.

2.5" female swivel rocker lug inlet coupling.



## STANDPIPE WYE 2.5" x 1.5" (65mm x 38mm)

2.5" (65mm) female swivel inlet x two 1.5" (38mm) male outlets. This wye is intended for use in high rise packs. One branch of the wye connects to the hose in the pack. The other branch has a quarter-turn aluminum ball valve for positive shutoff. A pressure gauge is mounted on top of the wye. Rugged, lightweight aluminum alloy casting with durable powder coat finish inside and out, anodized couplings and super tough folding nylon handles. 2.5" female rocker lug swivel inlet coupling is standard.



## FORESTRY 38mm (1.5") GATED WYE

Wye, 38 mm (1.5") NPSH For 1 into 2 operation. Unrestricted flow. Swivel nut rotates on ball bearings for ease of connection and to minimize cross threading. Designed to withstand 4 136 kPa (600 psi) test pressure. Light, corrosion resistant anodized alloy, painted bright red colour. Supplied with 38 mm (1.5") rubber gasket 12-43. One hard anodized rocker lug swivel hose fitting 38 mm (1.5") female NPSH inlet and two 38 mm (1.5") male NPSH outlet. 0,45 kg (1lb).



## WATERAX-WASA 2 10

Siamese Ball Valve, 38 mm (1 1/2") 1/4-Turn For 1 into 2 or 2 into 1 operation. Unrestricted flow. Equipped with 1/4-turn quick connection Designed to withstand 4 136 kPa (600 psi) test pressure. Two ball valves enable independent line control. Balls adjust automatically to compensate for wear. Corrosion resistant anodized alloy, Three 38 mm (1 1/2") openings with three 38 mm (1 1/2") instantaneous adaptors. 1.8 kg



## WATER THIEF- 65mm (2.5")

WATER THIEF 2.5" (65mm) X 2.5" (65mm) DUAL 1.5" (38mm) SIDE PORTS Quarter-turn aluminum ball valves provide a positive shutoff. Full flow 2.5" (65mm) and 1.5" (38mm) waterways provide maximum flow with minimal loss. Rugged lightweight aluminium alloy casting with durable powder coat finish inside and out, anodized couplings, super tough nylon folding handles and built in carrying strap. 2.5" (65mm) female swivel rocker lug inlet coupling is standard.



## MANIFOLDS

4 & 5 WAY MANIFOLDS - 4.0" STORZ x 4.0"STORZ and up to 6.0" available, Outlets 2.5"



### Contact Us

Phone 03 9464 8400

Email [gaam.au@tycoint.com](mailto:gaam.au@tycoint.com)

Website [www.gaam.com.au](http://www.gaam.com.au)