

Foam When You Want It, Protection When You Need It...



QuadraCup Selectable
Gallonge Nozzle

QuadraCup Selectable Gallonge
Nozzle Fog Pattern

... REALLY !

TFT's 1.5" QuadraCup selectable gallonge nozzle offers you a choice of 30, 60, 95 or 125 gpm with a retractable foam aspirating sleeve. The front end can be rotated from straight stream through wide fog patterns.

Sliding the metal front end forward produces venting for aeration of your foam solution. Nozzleman can adjust the pattern for reach and aspiration. Available in Tip Only, Ball Valve Shutoff and Ball Valve Shutoff with Pistol Grip.

Handle covers and Pistol Grips are available in NFPA colors. To learn more about the QuadraCup Series of Nozzles, contact your local TFT dealer today.



TASK FORCE TIPS
Made in USA • www.tft.com

3701 Innovation Way, Valparaiso, IN 46383-9327 USA
US & CN 800.348.2686 • 1.219.462.6161 • fax 1.219.464.7155



QuadraCup Nozzle
with Foam Aspiration
Sleeve Retracted

FQS125BC



QuadraCup Nozzle
with Foam Aspiration
Sleeve Engaged

Visit www.tft.com
to learn more.

1.5" (38 mm) QUADRACUP SERIES

30, 60, 95 & 125 gpm (110, 230, 360, & 470 l/min)

The QuadraCup is a rugged and dependable selectable gallonage nozzle with a retractable foam aspiration sleeve. When the outer sleeve is in the retracted position, the nozzle operates the same as the TFT QuadraFog. Flow can be set to any one of four flow settings, or to a flush mode. The front end can be rotated from straight stream through wide fog patterns. Uniquely cut fixed metal fog teeth produce a wide range of fog patterns.

To use the aspirating feature of the nozzle, the nozzle operator slides the outer sleeve forward, and by adjusting the pattern, has control of reach and aspiration. If an immediate wide fog pattern is needed, the sleeve can be retracted instantly to its regular position.

Available in either tip-only configuration or with a stainless ball shutoff, the QuadraCup is also available with optional colored pistol grip and handle covers (NFPA 1901 (A.16.9.1)). Metric calibrations available: 110-230-360-470 l/min @ 7 bar - consult factory for model numbers.

FQ125BC
FQ125BCL
1.7 lb. (0.7kg)
5.00" - 7.25"
(12.7-19.1cm)



FQ125BC QUADRACUP TIP 1.5" NH (38mm) - Selectable gallonage nozzle with four flow settings of 30, 60, 95, and 125 gpm @ 100 psi (110, 230, 360 and 470 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. This tip-only design has an "off" position for break-and-extend operations. 1.5" NH (38mm) rigid thread is standard.

FQ125BCL LOW PRESSURE VERSION - Same as FQ125BC but operates at a lower pressure 75 psi (5bar).

FQS125BC
FQS125BCL
3.0 lb. (1.3kg)
7.25" - 9.75"
(18.4-24.8cm)



FQS125BC QUADRACUP NOZZLE 1.5" NH (38mm) - Selectable gallonage nozzle with four flow settings of 30, 60, 95, and 125 gpm @ 100 psi (110, 230, 360 and 470 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Rocker lug 1.5" NH (38mm) swivel is standard.

FQS125BCL LOW PRESSURE VERSION - Same as FQS125BC but operates at a lower pressure 75 psi (5bar).

FQS125BCP
FQS125BCPL
3.2 lb. (1.5kg)
7.25" - 9.75"
(18.4-24.8cm)



FQS125BCP QUADRACUP W/GRIP 1.5" NH (38mm) - Selectable gallonage nozzle with four flow settings of 30, 60, 95, and 125 gpm @ 100 psi (110, 230, 360 and 470 l/min @ 7 bar). All lightweight materials, hardcoat anodized aluminum. Flush without shutting down. Quick-change rear valve seat and stainless steel shut-off ball. Pistol grip is mounted below the valve. Rocker lug 1.5" NH (38mm) swivel is standard.

FQS125BCPL LOW PRESSURE VERSION - Same as FQS125BCP but operates at a lower pressure 75 psi (5bar).

Folding Pistol Grip Kits with NFPA color inserts are available.