



WATER DELIVERY HARDWARE & ACCESSORIES


TASK FORCE TIPS
FIREFIGHTING EQUIPMENT

1-800-348-2686 ■ www.tft.com

Hardware & Accessories



Detent Elbow



Jumbo Gate PRV



Ball Intake Valve



By visiting www.tft.com, TFT's exclusive Web Key code provides immediate access to detailed specifications, a parts break down, pictures, users of the products in your area, and references from other fire suppression professionals on the specific product in which you are interested.

WATER
DELIVERY
HARDWARE &
ACCESSORIES



Ball Intake Valve Series

Web Key: AB

TFT's Ball Intake Valve is designed for use with 4", 4-1/2", 5" or 6" Large Diameter Hose (LDH).

- **2000 gpm flows with minimal loss**
- **Patented 30° swiveling inlet and ball-style valve with position indicator**
- **Unique polymer ring coupling attachment and triple-coating process for maximum corrosion resistance**
- **Ideal for drafting or pressure operations on pumper and aerial apparatus**

Swiveling Detent Elbow

Web Key: AD

Made from hard-anodized and powder-coated aluminum for maximum corrosion protection, these 30° intake elbows swivel 360° and have multiple positive detents.

- **Hose couplings are attached using TFT's unique polymer bearing rings, which also provide electrical isolation to help prevent galvanic corrosion**
- **Available with many combinations of Storz or threaded connections**

- **All 4" and 5" Storz couplings are forged from aluminum for ultimate strength**

- **Ideal for pumper or aerial apparatus with Master Intake Valves (MIVs)**

Jumbo Gate Valve Series

Web Key: AG

TFT's gate valve is designed for 4", 4-1/2", 5", or 6" LDH, enabling pressure or vacuum service for use on hydrant, pumper, or ground.

- **Unique stainless steel wedge-gate design results in low wear and reliable bi-directional sealing**
- **Hose couplings are attached using polymer bearing rings that provide electrical isolation to help prevent galvanic corrosion**
- **Available with many combinations of Storz and threaded connections**

Jumbo Gate with Elbow and Pressure Relief Valve (PRV)

- **The 30° elbow enables hose connections with minimal kinks and coupling stress**
- **Adjustable PRV, optional**
- **Available with many combinations of Storz or threaded connections**

Jumbo Siamese and Jumbo Wye Series

Web Key: AS

The Jumbo Siamese and Jumbo Wye series are designed for 3", 3-1/2", 4", 4-1/2", 5", or 6" LDH.

- **All Siamese appliances feature a clapper valve with indicator for visual check of clapper position (not available on Jumbo Wye). The clapper allows a second line to be added without interruption in water flow**
- **Three strategically placed legs allow the appliance to sit off the ground even with 6" Storz on inlet/outlet**
- **Large main housing provides superior strength and durability**
- **Hose couplings are attached using polymer bearing rings that provide electrical isolation to help prevent galvanic corrosion**

Common Features for All Hardware

- **Maximum operating pressure is 250 psi (17 bar)**
- **Meets 900 psi (62 bar) hydrostatic strength test**

For additional information call 1-800-348-2686, visit www.tft.com or contact your local authorized TFT distributor.



Jumbo Gate Valve



Jumbo Wye



Adapter



Pressure Relief Valve



Elbow

Adapters and Elbows

Web Key: AA

Adapters and Elbows (cast to a 30° down angle to relieve weight of the hose when connected) are designed for pressure or vacuum service for use on hydrant, pumper, or ground.

- *Maximum operating pressure is 250 psi (17 bar)*
- *Meets 900 psi (62 bar) hydrostatic strength test*
- *The aluminum parts are hard-coat anodized for maximum corrosion protection*
- *Hose couplings are attached using polymer bearing rings that provide electrical isolation to help prevent galvanic corrosion*
- *Available with many combinations of Storz and threaded connections*
- *All Storz couplings are forged from aluminum for ultimate strength*

Accessories

Web Key: AO

Blind Storz Caps

- *Made of lightweight, heat-treated aluminum*
- *Include an 18" lanyard with 1/4" eye for easy attachment*

- *Come with a suction gasket and no locking lever, NFPA 1963 standard compliant*

Pressure Relief Valves

- *Adjustable from 50 to 250 psi with easy-to-see 25 psi increments*
- *The aluminum casting is plastic impregnated, hard-coat anodized, and TFT powder-coat finished inside and out for maximum corrosion protection*

Hydrant Wrenches

- *Hydrant wrench is adjustable to open any hydrant configuration and has spanner shape that can be used on 4" and 5" Storz couplings*
- *Aluminum alloy construction with rugged grip*

Spanner Wrenches/Holder

- *Lightweight cast-aluminum alloy fits 2" through 5" Storz fire hoses and fittings*
- *Includes four wrenches and bracket for easy truck mounting*

Hose Rollers

- *Enables fast, easy removal of air and water from hose*
- *Constructed with all lightweight materials*

LOT-105



**2800 EAST EVANS AVENUE
VALPARAISO, INDIANA 46383-6940**



TYCO Australia PTY LIMITED (A.C.N. 008 399 004)
29 Temple Drive Thomastown Victoria 3074
Phone: +61 3 9466 1244 Fax: +61 3 9466 4743